



EoSens10MCX12-FM

EoSens® CoaXPress12

High-Speed with CoaXPress-12

Mikrotron CoaXPress-12 cameras comply with the CoaXPress 2.0 specification and transmit at 4 lanes up to 50Gbit/s. They meet the highest requirements for minimum latency and jitter. They satisfy most stringent requirements for minimum latency and jitter. The cameras are very light sensitive and support multiple binning modes and ROIs depending on the model.

Technical Highlights:

- scalable interface with 1, 2 or 4 connections
- complies with CoaXPress 2.0 standard, compatible with CXP 1.0 standard
- light sensitive sensor
- only 80 x 80 x 66 mm small
- Shock and vibration resistant



SPECIFICATIONS

Resolution [MP]	10 MP
Resolution (h x v)	4608 x 2176 px
Frame rate (max.)	482 fps
Chroma	mono
Interface	CXP-12 with 4 Connections

SENSOR

Sensor	Gsprint 4510
Manufacturer	Gpixel
Sensor type	Area CMOS
Sensor size (h x v)	20.74 x 9.79 mm
Optical diagonal	22.93 mm
Sensor format	4/3 "
Pixel size (h x v)	4.5 x 4.5 µm

FRAME RATES

4608 x 2176	478 fps
-------------	---------

CAMERA

Exposure modes	EXTERNAL
Trigger modes	Button, External TTL Signal, CXP-Trigger
Exposure time (min)	1 µs
Exposure time (max)	1 sec (external ∞)
Pixel format / max	mono8, mono12 / 12 bit
Dynamic range (max)	68.8 dB (dep. on environment)

FEATURE SET

AOI	yes
Binning	yes
Shading correction	yes
Defect pixel correction	yes
PoCXP	yes

HOUSING

Lens mount	F-Mount
Dimensions (w x h x d)	80 x 80 x 92.9 mm
Weight	630 g
Ambient temperature	-10 to 65 °C
Ambient humidity	10 to 90 % (non-condensing)
Protection class	IP30

I/O-INTERFACES

Input up to 24V	2 x
Input Galvanic	2 x
Output Galvanic	2 x
Power supply	12 to 24 V (DC)
Power consumption	18.5 W (dep. on operating mode)

